January 1, 2015

CAN BE USED AS A CUTOFF SAW CAN RIP CUT, NOTCH BLOCKS CAN CONTOUR CUT BLADE 1/4" TO 3/4" 3/4 HP BLADE DRIVE



•

**VERTICUT<sup>®</sup>-MODEL 115C GENERAL PURPOSE VERTICAL BANDSAW** 

BAXTER

INC.

ТМ

254 mm

VERTIGUT

254 mm X 330 mm

SHOWN WITH OPTIONAL

VARIABLE SPEED DRIVE

RECTANGULAR 10" X 13"

CAPACITY ROUND **• 10**"

•

**VERTICUT**®

**BANDSAW MACHINES** 

## VERTICUT<sup>®</sup> - MODEL 115C GENERAL PURPOSE VERTICAL BANDSAW



CUTTING CAPACITY	
Round	10" (250 mm)
Round with Maximum 8 1/2" (216 mm) Length	13" (330 mm)
Round at 45°	7" (180 mm)
Rectangular	10" x 13" (250 x 330 mm)
Rip Cutting Width	9" (230 mm)
SPECIFICATIONS	
Blade Size	1/4" to 3/4" x 10' (6 to 19 mm x 3050 mm)
Blade Speeds	75,130, 215, 350 ft/min (23, 40m 66, 107 m/min)
Blade Tension	30,000 psi
Table Height	33" (840 mm)
Work Table (Ground Solid Steel	1" x 18" x 30" (24 mm x 460 mm x 760 mm)
Machine Weight	1,000 lb. (455 kg)
Overall Dimensions	34" x 48" x 68" (860 mm x 12250 mm x 1730 mm)
DRIVE	
Blade Drive	3/4 Hp (.56 kW)
Motor Starter	Manaul
Voltage available (single phase)	115 Volts
FEATURES INCLUDED AS STANDARD EQUIPMENT	
<ul> <li>Can be used as a cut-off saw,</li> <li>Can rip cut, can notch blocks</li> <li>Can contour cut as a tool room saw</li> <li>Foot pedal for hands free carriage movement of 4" (100 mm)</li> <li>Graduated scale for depth of cut</li> <li>Miter block allows miter cutting of +/- 45°</li> <li>C-clamp for clamping of material</li> <li>Adjustable cutting force for cutting of solids or structural shapes</li> <li>Ground solid steel table</li> <li>Heavy duty base for stability and strength</li> <li>Adjustable material length stop for repetitive cutting</li> <li>Cast iron wheels</li> </ul>	<ul> <li>Roller guides are hardened and grooved allowing use of 1/4", 3/8", 1/2" and 3/4" (6.4, 9.5, 12.7, 19 mm) blades without any adjustment</li> <li>Gear box designed for heavy duty bandsaw machines, precision machined worm and phosphorous bronze worm gear set supported on sealed ball bearings, grease packed</li> <li>All bearings are totally enclosed and lubricated for life</li> <li>Electric system uses only C.S.A./UL approved components and is electrically approved</li> <li>Premium quality bandsaw blade</li> <li>Instruction and parts manual</li> </ul>
OPTIONS	
Single Phase Magnetic Starter	
End of Cut Shut Off	
Electronic Variable Speed Drive (1 hp) Laser light cut indicator	

Material Stand Conveyor 10' long

Crating Charge

Due to Baxter Verticut's policy of continuous improvement we reserve the right to make any changes to the machine without incurring any obligations. Machine shown may have optional equipment installed.

The machine warranty is for a period of one year from date of purchase, some exceptions apply, contact the manufacturer for full details. This price list supersedes all previous price lists. All taxes are extra. Unless prior arrangements have been made terms are C.O.D. Machines are F.O.B. our plant.